


# Air Filter Regulators YT-200 / YT-205 / YT-220 / YT-225

## Design features


- **Stable output and repeatability.** Provides constant control under variable flow rates and supply pressures.
- **Relief flow capability.** Discharges pressure if outer pressure is higher than set pressure.
- **Light weight and compact size.** Reduces installation costs.
- **Five micron filter.** Protects pneumatic instruments from dirty air.
- **Manual or auto draining option**



YT-200 / YT-205 Flow (LPM)



YT-220 / YT-225 Flow (LPM)



Item Type	YT-200	YT-220	YT-205	YT-225
Max. Supply Pressure	1.7 MPa = 17 bar = 246.5 psi			
Max. Output Pressure	0.42 MPa (A Type), 0.84 MPa (B Type) 60.9 psi (A Type), 121.8 psi (B Type)			
Air Connection	Rc 1/4, 1/4 NPT	Rc 1/2, 1/2 NPT	1/4 NPT	1/2 NPT
Gauge Connection	Rc 1/4, 1/4 NPT	Rc 1/4, 1/4 NPT	1/4 NPT	1/4 NPT
Operating Temp.	-20 to +70 °C (-4 to +158 °F) (Standard type)			
Min. Filtering Size	5 micron			
Material	Aluminium Diecasting		Stainless Steel 316	
Weight (Manual drain)	0.62 kg (1.4 lb)	0.88 kg (2 lb)	1.5 kg (3.3 lb)	2.2 kg (4.8 lb)

## Product Code

YT-200 - A - N - 0 - 1 - 0

### Model

YT-200 = Aluminium 1/4"  
YT-205 = Stainless Steel 1/4"  
YT-220 = Aluminium 1/2"  
YT-225 = Stainless Steel 1/2"

### Adjustable Range

A = 0 to 0.42 MPa  
B = 0 to 0.84 MPa

### Connection Type

P = Rc (N/A for YT-205/225)  
N = NPT

### Gauge

0 = None  
1 = 0 to 0.4 MPa  
2 = 0 to 1.0 MPa

### Operating Temp.


1 = -20 to +70 °C (-4 to +158 °F) (N/A for EAC)  
2 = -20 to +120 °C (-4 to +248 °F) (N/A for EAC)  
3 = -40 to +70 °C (-40 to +158 °F)  
4 = -50 to +70 °C (-58 to +158 °F) (only EAC)

### Option


0 = Manual drain  
1 = Auto drain<sup>1</sup>

### Notes:


1. Only "1" of Operating Temp. is available




YT-200/205 Manual drain



YT-200/205 Auto drain



YT-220/225 Manual drain



YT-220/225 Auto drain